

The new PLUS series from 80 hp to 117 hp

EVERYONE DESERVES A **PLUS**



Your partner to rely on.

STEYR
TRAKTOREN

THE ULTIMATE ALL-ROUND **VERSATILITY**

An iconic product name of the STEYR brand, the PLUS series returns to create a powerful link between our rich history and strong future.



The result: PLUS, more than you expect, just what you deserve

The ultimate all-round versatility for today's modern mixed and livestock farms. Whether it is doing loader work, working with front or rear mounted implements, transport, or even in confined spaces, the PLUS delivers maximum performance and comfort.

The bold and dynamic look express the force of our modern design, that makes it look like larger high-power tractors.

A 3.6 l FPT Industrial engine, with power from 80 to 117 hp, gives a wide choice of models to fit all end users' needs.

» It does it all, better.



EASE OF USE IS A **GREAT PLUS**



Axle-guided front hitch.



Impressive manoeuvrability with the Powershuttle.



Class 1.0 HD and 1.5 HD front axles ideal for intensive loader work.



Combinations of tyres and wheels to suit every type of application.



40 kph ECO- speed on S-Control 2 transmission for reduced fuel consumption.



Increased Gross Vehicle Weight of 7,000 kg.



S-Control 2 - 24x24 2-speed Powershift transmission with Powershuttle.



Ergonomic operation using the Multicontroller.



FieldOps™ lets you remotely monitor and manage your farm, fleet and data.



High lift capacity of up to 4,700 kg with increased capacity 82 l/min pump.



Superlative visibility with Hi-Visibility roof panel and redesigned exhaust.



S-Guide Autoguidance ensuring up to 1.5 cm pass-to-pass and year-over-year accuracy.



New suspended cab.



Loader Ready with complete loader package from factory.



S-Stop Clutch for smooth control of the tractor and Stop & Go functionality.



Mechanical Front Hitch with front PTO.



Variable Ratio Steering reducing the lock-to-lock turns of the steering wheel.



Mechanical Draft Control or Electronic Draft Control.



Lift-O-Matic system offers fast implement raising and lowering.

GET A PLUS IN **ALL SUBJECTS**



Plus in versatility

Class 1.0 HD and 1.5 HD front axles to suit all needs, complete loader package from factory for loader plug-and-play, up to 16.9 R38 tyres and increased Gross Vehicle Weight of 7,000 kg emphasise the multiform talent of this series.




Plus in productivity

Powerful and efficient 3.6 l FPT Industrial engine with power from 80 to 117 hp, 82 l/min pump for increased responsiveness, up to 4,700 kg lift capacity, and new light package provide the right equipment to produce more with less.



Plus in comfort

New cab suspension for a smooth ride, new clear display of the machine's parameters and settings, Hi-Visibility roof panel, S-Stop and Variable Ratio Steering help to make long working days much more comfortable.



Plus in precision

S-Guide Autoguidance ensures up to 1.5 cm pass-to-pass and year-over-year accuracy, allowing accurate application of production inputs. With FieldOps™, agronomic decisions can be taken on-the-go thus improving productivity and efficiency.

MODEL	4080 PLUS	4090 PLUS	4100 PLUS	4110 PLUS	4120 PLUS
-------	-----------	-----------	-----------	-----------	-----------

TRANSMISSION											
S-Control 2 – 24x24 2-speed Powershift with Powershuttle, 40 kph											
ENGINE											
FPT F5 3.6 l Common Rail Diesel engine, turbocharged and intercooled / HI-eSCR2 technology / Stage V Number of cylinders / Capacity [cm ³]		4 / 3,600		4 / 3,600		4 / 3,600		4 / 3,600		4 / 3,600	
Max. engine power ECE R120 ¹⁾ [kW/hp]	Rated engine power ECE R120 ¹⁾ [kW/hp]	59 / 80	59 / 80	66 / 90	66 / 90	74 / 100	74 / 100	81 / 110	81 / 110	86 / 117	86 / 117
Engine speed at max. engine power [rpm]	Rated engine speed [rpm]	1,900	2,300	1,900	2,300	1,900	2,300	1,900	2,300	1,900	2,300
Max torque [Nm @ 1,300 rpm]		330		380		450		490		506	
Torque increase OECD [%]		34.7		38.7		46.5		45.7		41.7	
HYDRAULIC											
Open Center pump up to 82 l/min Up to 3 mechanical rear remotes 2 mechanical mid mounts, joystick Lift-O-Matic system offers fast raising and lowering											
PTO											
540 / 540E / 1,000 @ 1,938 / 1,535 / 1,926 rpm											
REAR LINKAGE											
MDC Mechanical Draft Control or EDC Electronic Draft Control - max. lift capacity 4,700 kg											
CONFIGURATION											
Mechanical front hitch with front PTO STEYR S-front loader, new U range with quick coupler, vibration damping & collision protection S-Stop (Brake to clutch)											

¹⁾ ECE R120 complies with ISO 14396 and 97/68EC

You drive better when you are safe. Before using this vehicle, please read the Operating Manual and become familiar with the use of each of the controls. Note the contents of the instruction panels and use the safety equipment for your own personal safety. This brochure is intended for use internationally. The availability of a few models and of standard and special equipment items may vary from one country to another.



STEYR reserves the right at any time and without prior announcement to make changes to the design and technical version without this in any way obliging STEYR to transfer these to units already sold.

Details, descriptions and pictorial material reflect the current status at the date of publication, but can be amended without prior announcement and at any time. Pictorial materials may show certain national versions, items of special equipment as well as non-complete standard versions.

TP01 / SM / 10.24 / Printed in Austria – Cod. n. 24S0003COMINB
www.steyr-traktoren.com

steyr-traktoren.com



STEYR
TRAKTOREN