

MODEL	6360 CERVUS CVT	6390 CERVUS CVT	6440 CERVUS CVT
<b>ENGINE</b>			
No. of cylinders / Aspiration / Valves	6 / eVGT / 4	6 / eVGT / 4	8 / eVGT / 4
Capacity [cm <sup>3</sup> ]	8,700		
Rated engine speed [rpm]	2,000		
Rated power @ 2,000 [hp]	360	390	435
Maximum power @ 1,800 [hp]	360	390	435
Maximum torque @ 1,400 [Nm]	1616	1750	1851
Diesel tank capacity [Litres]	680		
AdBlue® tank capacity [Litres]	93		
Service interval [hours]	750		
<b>TRANSMISSION</b>			
Type	S-Control™ CVT Continuously Variable Transmission		
Max. speed [kph]	40 / 50 / 60		
Engine speed at 40 / 50 / 60 kph [rpm]	1,195 / 1,495 / 1,790		
<b>PTO</b>			
Rear PTO engine speed at 540E / 1,000 [rpm]	1,598 / 1,852		
Rear PTO engine speed at 1,000 / 1,000E [rpm]	1 852 / 1 567		
Front PTO engine speed at 1,000 / 1,000E [rpm]	1,886 / 1,585		
<b>LINKAGE</b>			
Rear linkage category	III / IVN		
Maximum rear lift capacity at ball ends [kg]	11,760		
Front linkage category	IIIN		
Maximum front lift capacity at ball ends [kg]	5,800		
<b>AXLES</b>			
Independent front axle suspension	Double wishbone design for comfort and high load capacity		
Turning radius measured at the drawbar pin [mm]	6,100		
<b>DIMENSION</b>			
Length – Rear lower links horizontal to front top link [mm]	5,732		
Height	Middle of rear axle to top of roof [mm]	2,374	
	Middle of rear axle to top of GPS Antenna [mm]	2,474	
Width – Over rear fenders without extension [mm]	2,848		
<b>WEIGHT</b>			
Weight base specification [kg]	12,450		

You drive better when you are safe. Before using this vehicle, please read the Operating Manual and become familiar with the use of each of the controls. Note the contents of the instruction panels and use the safety equipment for your own personal safety. This brochure is intended for use internationally. The availability of a few models and of standard and special equipment items may vary from one country to another.



STEYR reserves the right at any time and without prior announcement to make changes to the design and technical version without this in any way obliging STEYR to transfer these to units already sold.

Details, descriptions and pictorial material reflect the current status at the date of publication, but can be amended without prior announcement and at any time. Pictorial materials may show certain national versions, items of special equipment as well as non-complete standard versions.

TP01 / SM / 10.25 / Printed in Austria – Cod. n. 2550001COMINB

[www.steyr-traktoren.com](http://www.steyr-traktoren.com)

[steyr-traktoren.com](http://steyr-traktoren.com)



**STEYR**  
TRAKTOREN