

ZG-TS

Technical data

ZG-TS trailed spreaders

Model	ZG-TS 7501 ProfisPro	ZG-TS 10001 ProfisPro
Working width (m)	15–54	
Hopper capacity (l)	7,500	10,000
Permissible total weight (kg)	12,500	12,500
Max. payload (kg)	8,650	8,500
Filling height (m) + static tyre radius	1.71	1.98
Filling width (m)	4.09	
Filling depth (m)	1.94	
Overall length (m)	7.33	
Total width (m), (depending on the tyres fitted)	2.48–2.90	
Total height (m), (depending on the tyres fitted)	2.68–3.03	2.95–3.30
Spreading disc drive options	Hydraulic-drive with oil supplied exclusively from the tractor Oil requirement with steering axle max. 130 l/min Oil requirement without steering axle max. 105 l/min Hybrid drive with combined oil supply Oil requirement with steering axle max. 85 l/min Oil requirement without steering axle max. 60 l/min	
Weighing system	ProfisPro c/w FlowControl torque measuring system	
Min. weight (kg) (without optional equipment)	3,850	4,000

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.

Spreading lime and fertiliser with the ZG-TX

The ZG-TX combi spreader from AMAZONE can spread both lime and fertiliser. The spreading unit on the machine can be quickly converted for lime. Lime is then efficiently spread over working widths of up to 16 metres with hopper capacities of between 6,800 litres and 11,200 litres. Further information can be found in the additional brochure “ZG-TX combi spreader”.

