



## Technical data:

### TopCut 12000-2T cutting roller combination

Model	TopCut 12000-2T
Working width (m)	12.10
Transport width (m)	3.00
Transport height (m)	3.80
Transport length with lighting for road transport (m)	8.30
Operational speed (km/h)	14 – 20
Depth of work (cm)	0 – 3
Disc spacing (mm)	20
Minimum TillDisc disc spacing (cm)	10
Disc diameter (mm)	410
3-row harrow tine spacing (cm)	10
Harrow tine thickness (mm)	14
Transport wheel tyre dimensions	550/45-22.5
Number of double-acting spool valves (min/max)	2/4
Power requirement from (kW/hp)	180/240
Linkage	Drawbar eye or K80
Weight of the base machine without rear element (kg)	5,900



Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



**AMAZONEN-WERKE H. DREYER SE & Co. KG**

P. O. Box 51 · 49202 Hasbergen-Gaste/Germany  
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193